advetage solutions

A Disabled Veteran Owned Small Business

GUARDIAN™ ULTRA-VIOLET NITRILE GLOVES

ULTRA FEATURES

- **ENHANCED STRENGTH:** 6mil thick for added protection from tears and leaks
- **MAXIUM PROTECTION:** 12" length, Can be worn over gown cuffs for added protection
- **CHEMICAL RESISTANCE:** tested for resistance to penetration from chemo-therapy drugs and fentanyl per ASTM D6978
- **MEDICAL GRADE:** Conforms to ASTMD 6319 , FDA 510(K) Registration
- **FINGER TEXTURED:** Enhanced grip and tactile sensitivity
- **ACCELERATOR-FREE NITRILE:** no natural latex, reducing the risk of skin irritation
- **BEADED CUFF:** reduced risk of roll downs and allows for easier donning and doffing
- **CHLORINATED & POWDER-FREE**
- **COLOR:** Nobel-Violet
- **HIGHEST QUALITY STANDARDS:** Manufactured to ISO 9001, 13485:2016, and MDSAP quality mgmt. system.



The Guardian ULTRA-VIOLET nitrile gloves offer ultimate protection with-out sacrificing comfort or durability. These 6mil extended cuff have are finger textured for enhanced grip and tactile sensitivity, making them the perfect choice for workers in healthcare, sciences, industrial applications and first responders. They are rigorously tested to the highest industry standards and provide resistance to cytotoxic drugs, and Fentanyl

Meets **NFPA standards for Single-Use Emergency Medical Examination Gloves*

111 Penn St. Ste 202, El Segundo, CA 90245 | (424) 292- 8432 | www.advetage.com/GUARDIAN | customerservice@advetage.com

PHYSICAL DIMENSIONS

SIZE	PALM WIDTH	LENGTH	THICKNESS AT PALM	THICKNESS AT FINGER	THICKNESS AT CUFF
SMALL	3.0”- 3.4”	12”	5.5 mil	6.3 mil	4.8 mil
MEDIUM	3.4”- 3.8”	12”	5.5 mil	6.3 mil	4.8 mil
LARGE	3.8”- 4.2”	12”	5.5 mil	6.3 mil	4.8 mil
X-LARGE	4.2”- 4.6”	12”	5.5 mil	6.3 mil	4.8 mil
INSPECTION LEVEL/ AQL	ASTM D 3767, ASTM D 6319				

The information on this document is a guideline of typical values and characteristics of the product

QUALITY & CONFORMITY

CHARACTERISTIC	VALUE		TEST METHODS
Freedom from holes and liquid penetration	GI/AQL 1.5		ASTM D3578, D5151, F1671
Major Visual Defects	GI/AQL 2.5		ASTM D3578
Minor Visual Defects	GI/AQL 4.0		ASTM D3578
Residual Powder	<2.0 mg/glove		ASTM D6124
TENSILE PROPERTIES	**TENSILE STRENGTH**	**ULTIMATE ELONGATION**	
Before aging	>14 Mpa	500% nominal	ASTM D412a
After accelerated aging	>14 Mpa	400% nominal	ASTM D412a & D573

50 GLOVES PER BOX	10 BOXES PER CASE	500 GLOVES PER CASE

WE HELP MEET YOUR SUPPLIER DIVERSITY NEEDS

Advetage Solutions is a Certified Disabled Veteran Owned Small business and a SBA 8 (a) Certified Small Business

111 Penn St. Ste 202, El Segundo, CA 90245 | (424) 292- 8432 | www.advetage.com/GUARDIAN | customerservice@advetage.com